

EN

Please read these instructions carefully before using this safety clothing. You should also consult your safety officer or immediate superior with regard to suitable garments for your specific work situation. Store these instructions carefully so that you can consult them at any time.

CE

Refer to the product label for detailed information on the corresponding standards. Only standards and icons that appear on both the product and the user information below are applicable. All these products comply with the requirements of Regulation (EU 2016/425).



ISO 13688-1:2013

Protective Clothing (see label)

General Requirements. This European Standard specifies general requirements for ergonomics, ageing, sizing, marking of protective clothing and for information supplied by the manufacturer.

A = Recommended height range of wearer

B = Recommended chest girth of wearer

C = Recommended waist girth of wearer

D = Recommended inside leg measurement in any other way



EN 1149 Protective Clothing with Electrostatic Properties

This Standard specifies electrostatic requirements for electrostatic dissipative protective clothing to avoid incendiary discharges.

This Standard is not applicable for protection against mains voltages.

EN 1149-5 : 2018

Performance requirements for fabrics and garments.









EN 61340-5-1:2007

Garment meets requirement specified in Table 3 for point to point resistance.

Limits of Use (EN 1149):

Garments must be worn with trousers or upper body garments also meeting the standards. There should be sufficient overlap between upper and lower garments to ensure no gaps in protection. Non conforming garments worn over the garment will eliminate effectiveness.

Wash Care Labels : Refer to garment label for corresponding washing details.

-  Max temp 30°C, mild process
-  Max temp 40°C, mild process
-  Max temp 40°C, normal process
-  Max temp 60°C, normal process
-  Do Not Bleach
-  Do not tumble dry
-  Tumble dry low
-  Tumble dry normal

Always Worn Elsewhere:

- Workers wearing electrostatic dissipative protective clothing should be properly earthen. The resistance between the person and the earth shall be less than 10⁸, e.g. by wearing adequate footwear.
- The electrostatic dissipative protective clothing shall not be open or removed whilst in the presence of flammable or explosive atmosphere or whilst handling flammable or explosive substances.
- No modification of this garment e.g. adding logos is allowed after EC Type Approval. The electrostatic dissipative performance of the electrostatic dissipative protective clothing can be affected by wear and tear, Laundering and possible contamination.
- The electrostatic dissipative protective clothing shall not be used in oxygen enriched atmospheres without prior of the responsible safety engineer.
- This garment is suitable for wear during an entire working day and contains no toxic substances that can be a reach health adversely in any other way. No allergic reactions due to skin contact with this garment are known.
- Do not attempt to repair damaged garments.

Available Size & Selection:

Fit according to correct chest and waist size, refer to size chart. These garments have built in allowance for comfort and to allow the garment to be worn over medium bulky clothing. To obtain overall protection, the wearer may need to wear gloves (to EN 407 or EN 12477), Boots (to EN 20345) and or Safety helmet (to EN 397).

Storage:

DO NOT store in places subject to direct or strong sunlight. Store in clean, dry conditions.

After-care:

The manufacturer will not accept liability for garments where care labels have been ignored, defaced or removed.

Fibre Content Label:

Refer to garment label for corresponding content details.

Warning:


Where there is a hood, peripheral vision and hearing may be impaired.

REF: 77U5P



EN 1149
CERTIFIED

	A		D	
	CM	CM	CM	CM
SHORT	152-164	74		
REG	164-176	79		
TALL	176-188	84		
X TALL	188-202	92		



B	INCHES	CM	EURO
XS	32"-34"	80-88	40-44
S	36"-38"	92-96	46-48
M	40"-41"	100-104	50-52
L	42"-44"	108-112	54-56
XL	46"-48"	116-124	58-62
XXL	50"-52"	128-132	64-66
3XL	54"-55"	136-140	68-70
4XL	56"-58"	144-148	72-74
5XL	60"-64"	152-160	76-80

C	INCHES	CM	DE	FR
XS	26-28	68-72	42-44	34-36
S	30-32	76-80	46-48	38-40
M	33-34	84-88	50	42-44
L	36-38	92-96	52-54	46-48
XL	40-41	100-104	56	50-52
XXL	42-44	108-112	58-60	54-56
3XL	46-47	116-120	62	58-60
4XL	48-50	124-128	64-68	62-64

MANUFACTURER

PORTWEST, WESTPORT, CO MAYO, IRELAND

TEST HOUSE

INTERTEK

The Warehouse, Brewery Lane, Leigh, WN7 2RJ UK

Notified body number: 0362

SATRA

Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom **Notified body number: 0321**
Bractown Business Park, Clonee, Dublin 15, D15 YN2P Ireland
Notified Body: 2777

VARTEST

Vartest Laboratories, Inc., 19 West 36th Street,
10th Floor New York, NY 10018, ISO/IEC 17025 Testing Certificate No. through AZLA is 2180.01

AITEK

Plaza Emilio Sala 1, 03801 Alcoy, Alicante, Spain

Notified body number: 0161

OTI

Institut für Ökologie, Technik und Innovation GmbH, Spengergasse 20 1050 Vienna, Austria **Notified body number: 0534**